



PN: A0200004FP200AKR

DWG #:DB20-028 Rev0.3

SPECIFICATION

PRODUCT: Loudspeaker

STETRON PART NUMBER: A0200004FP200AKR

DESCRIPTION: Φ 200mm / 4 ohms / 10W / RoHS

RFQ: QB19200

STETRON APPROVALS	PREPARED BY	CHECKED BY	APPROVED BY
SIGNATURE	<i>RS</i>	<i>CS</i>	<i>CS</i>
DATE	15-Aug-2024	15-Aug-2024	15-Aug-2024

CUSTOMER APPROVAL	SIGNATURE	DATE

STETRON

90 Broadway, Buffalo, NY USA 14203-1687
2651 John Street, Unit 4, Markham Ontario, L3R 2W5

Phone (USA): + (716) 854-3443

Fax: + (716) 854-3448

Email: contact@stetron.com

Phone (Canada): + (905) 475-6202

Fax: + (905) 475-1926

Website: www.stetron.com

CONFIDENTIAL



PN: A0200004FP200AKR

DWG #:DB20-028 Rev0.3

REVISION HISTORY

Rev Level	Date	Description	Page #	Changed By
0.0	17-July-2020	Original	All Pages	RS
0.1	26-Sept-2022	General spec update	All Pages	RS
0.2	28-June-2023	Added packaging and removed preliminary stamp	All Pgs.	RS
0.3	15-Aug-2024	Updated frame dimensions	Pg. 7	RS





Contents

1. Scope -----	2
2. Environmental Requirements-----	2
3. Environmental test conditions -----	2
4. Electrical Requirements-----	2
5. Acoustical Requirements -----	3
6. Reliability -----	5
7. Mechanical Layout and Dimensions-----	7
8. Packaging -----	8

STETRON

90 Broadway, Buffalo, NY USA 14203-1687

2651 John Street, Unit 4, Markham Ontario, L3R 2W5

Phone (USA): + (716) 854-3443

Fax: + (716) 854-3448

Email: contact@stetron.com

Phone (Canada): + (905) 475-6202

Fax: + (905) 475-1926

Website: www.stetron.com

**1. Scope**

This document contains the required electrical, acoustic, mechanical and reliability information for a loudspeaker.

2. Environmental Requirements

This loudspeaker including all components, solder joints and glue must be RoHS compliant and meet the customer's known requirements for banned or restricted substances.

3. Environmental test conditions

	Standard Conditions	Preferred Conditions
Temperature	15 to 35°C	20 ± 2°C
Humidity	25 to 75%	63 to 67%
Air Pressure	86 to 106kPa	86 to 106kPa

Note: Conditions for Acoustic tests only

4. Electrical Requirements**4.1 Rated Impedance**

4Ω ±20% (@250Hz/1Vrms)

4.2 Rated Power

10.0W (RMS)

4.3 Max Power

15.0W (RMS)

4.4 Polarity

When a positive DC current is applied to the positive terminal of the speaker the diaphragm shall move forward.

STETRON

90 Broadway, Buffalo, NY USA 14203-1687

2651 John Street, Unit 4, Markham Ontario, L3R 2W5

Phone (USA): + (716) 854-3443

Fax: + (716) 854-3448

Email: contact@stetron.com

Phone (Canada): + (905) 475-6202

Fax: + (905) 475-1926

Website: www.stetron.com



5. Acoustical Requirements

5.1 Sound Pressure Level

90 ± 3dB (on IEC 268-5 Baffle in anechoic chamber @ 1W/1m avg. @ 0.2, 0.4, 0.6, and 1.0 kHz)

5.2 Resonant Frequency (F₀)

70 ± 20% Hz @ 1V_{rms} constant voltage - free air

5.3 Frequency Range

F₀ to 5 kHz (SPL -10dB) @ 1W/1m

5.4 Buzz and Rattle

No audible buzzing shall occur at ≥0.3m distance when 10W power (6.32V_{rms}) sine wave from F₀ to 2kHz is applied to the speaker.

*See Test circuit (Fig 1), Frequency Response (Fig 2), and Impedance (Fig 3) below.

STETRON

90 Broadway, Buffalo, NY USA 14203-1687

2651 John Street, Unit 4, Markham Ontario, L3R 2W5

Phone (USA): + (716) 854-3443


Fax: + (716) 854-3448

Email: contact@stetron.com

Phone (Canada): + (905) 475-6202

Fax: + (905) 475-1926

Website: www.stetron.com



STETRON

90 Broadway, Buffalo, NY USA 14203-1687

2651 John Street, Unit 4, Markham Ontario, L3R 2W5

Phone (USA): + (716) 854-3443

Fax: + (716) 854-3448

Email: contact@stetron.com

Phone (Canada): + (905) 475-6202

Fax: + (905) 475-1926

Website: www.stetron.com




Fig 3. Typical Free air impedance with 1Vrms

6. Reliability

6.1 High Temperature

Speakers are exposed in the high temperature chamber at $+70 \pm 2^\circ\text{C}$, R.H $25\% \pm 5\%$ for 16 hrs.

6.2 Low Temperature

Speakers are exposed in the low temperature chamber at $-25 \pm 2^\circ\text{C}$ (humidity random) for 16 hrs.

6.3 Humidity

Speakers are exposed to $+25 \pm 2^\circ\text{C}$, R.H $95\% \pm 5\%$ for 16 hrs.

STETRON

90 Broadway, Buffalo, NY USA 14203-1687

2651 John Street, Unit 4, Markham Ontario, L3R 2W5

Phone (USA): + (716) 854-3443

Fax: + (716) 854-3448

Email: contact@stetron.com

Phone (Canada): + (905) 475-6202

Fax: + (905) 475-1926

Website: www.stetron.com



*Note: After any of tests 6.1 to 6.3 leave speakers for 1 hr at room temperature.

Speakers must pass pure sound listening and appearance tests.

6.4 Rated Power

Speakers are exposed continuously to 10W pink noise for 8 hrs with 50 Hz low cut filter.

6.5 Max Power

Speakers are exposed to 15W pink noise (with 50Hz low cut filter) for 1 minute on and 2 minutes off for a total of 10 cycles.

Note: After test 6.4-6.5 leave speakers at room temperature for 1 hour. Speakers must pass pure sound listening, appearance test and the SPL should not deviate by more than ± 3 dB.

STETRON

90 Broadway, Buffalo, NY USA 14203-1687

2651 John Street, Unit 4, Markham Ontario, L3R 2W5

Phone (USA): + (716) 854-3443

Fax: + (716) 854-3448

Email: contact@stetron.com

Phone (Canada): + (905) 475-6202

Fax: + (905) 475-1926


Website: www.stetron.com



PN: A0200004FP200AKR

DWG #:DB20-028 Rev0.3

7. Mechanical Layout and Dimensions



All dimensions in mm

STETRON

90 Broadway, Buffalo, NY USA 14203-1687

2651 John Street, Unit 4, Markham Ontario, L3R 2W5

Phone (USA): + (716) 854-3443

Fax: + (716) 854-3448

Email: contact@stetron.com

Phone (Canada): + (905) 475-6202

Fax: + (905) 475-1926



Website: www.stetron.com




PN: A0200004FP200AKR

DWG #:DB20-028 Rev0.3

8. Packaging



After speaker is wrapped in cardboard put in outer box as per the above, 12 pcs per layer, 1 layer per box, 12 pcs total



Notes about the pallet

6 carton boxes/layer, 6 layers/pallet, 36 boxes per pallet
Gross weight 9kg per box. total weight per pallet is 380kg+/-10%. 12pcs per carton, 432pcs per pallet
When stacking, gaps (between boxes) for the upper layer and lower lay should stagger
Wrap with plastic film firmly for at least 3 rounds on the 4 sides and top
Pack with protective cardboard corners on the edges with packing strap in "# shape

All dimensions in mm



STETRON

90 Broadway, Buffalo, NY USA 14203-1687

2651 John Street, Unit 4, Markham Ontario, L3R 2W5

Phone (USA): + (716) 854-3443

Fax: + (716) 854-3448

Email: contact@stetron.com

Phone (Canada): + (905) 475-6202

Fax: + (905) 475-1926

Website: www.stetron.com